



TECHNICAL DATA SHEET

/// FLEXSTOR® II - 1U

GENERAL

Drive Type	Half-height LTO-3, -4, -5 or -6
Interface Type	SCSI, SAS or Fibre Channel
Media Type	Ultrium-3, -4, -5 or -6 (Drive dependent)

FORM FACTOR

19" rack mount	1 rack Unit high
----------------	------------------

CONFIGURATION

Drive Capacity	1 half-height LTO
Slot Capacity	8
Mailslot Quantity	1
Number of Magazines	2

CAPACITY

Native Capacity	20 TBytes (LTO-6)
Compressed Capacity (2,5:1)	50 TBytes (LTO-6)

SPEED

Transfer Rate	Drive and interface dependent
---------------	-------------------------------

RELIABILITY

Robotic MCBF	500,000 Cycles
--------------	----------------

ACCESS AND OPERATION

Front Operator Panel	Password-protected with menus for configuration, management, status and diagnostics
Remote Management Interface	Via standard Ethernet connection Password-protected with menus for configuration, management, status and diagnostics

TECHNICAL DATA SHEET

/// FLEXSTOR® II - 1U

POWER

Power Supply Quantity	1
Input Voltage	100-240 VAC (50-60 Hz)
Power Consumption	80W (Bronze 80 Plus - Green Power Supply)

ENVIRONMENTAL REQUIREMENTS

Noise Emissions	≤ 5.8dB
Vibration	0.21 Grms 5-500 Hz (operating)
Operating Temperature	10°C bis 35°C
Operating Humidity	20% to 80% (non-condensing)

PHYSICAL DIMENSIONS

Width	447.5 mm (17.62 inches)
Depth	740 mm (29.13 inches)
Height	43,8 mm (1,73 inches)
Weight	10kg* (22lbs) *without tapes

