



## FLEXSTOR II – 2U

### GENERAL

Drive Type	Half-height, Full-height LTO -5, -6, -7, -8, -9
Interface Type	SCSI, SAS or Fibre Channel
Media Type	Ultrium -5, -6, -7, -8, -9 (Drive dependent)

### FORM FACTOR

19" rack mount	2 rack Unit high
----------------	------------------

### CONFIGURATION

Drive Capacity	1 full-height LTO or 2 half-height LTO
Slot Capacity	24
Mailslot Quantity	1
Numbers of Magazine	2

### CAPACITY

Native Capacity	432 TBytes (LTO-9)
Compressed Capacity (2,5:1)	1080 TBytes (LTO-9)

### SPEED

Transfer Rate	Drive and interface dependent
---------------	-------------------------------

### RELIABILITY

Robotic MSBF	1,000,000
--------------	-----------

**FLEXSTOR II – 2U****ACCESS AND OPERATION**

Front Operator Panel	Password-protected with menus for configuration, management, status and diagnostics
Remote Management Interface	Via standard Ethernet connection Password-protected with menus for configuration, management, status and diagnostics

**POWER**

Power Supply Quantity	1
Input Voltage	100-240 VAC (50-60 Hz)
Power Consumption	160W

**ENVIRONMENTAL REQUIREMENTS**

Noise Emission	≤ 5.8dB
Vibration	0.21 Grms 5-500 Hz (operating)
Operating Temperature	10°C bis 45°C
Operating Humidity	10% to 80% (non-condensing)

**PHYSICAL DIMENSIONS**

Width	447.5 mm (17.62 inches)
Depth	810 mm (31.9 inches)
Height	97,6 mm (3,84 inches)
Weight	22kg* (49lbs) *without tapes